- Plug-in cardan shaft for easy worm part replacement
- Infinitely adjustable delivery rate
- Mounted pan mixer, ideal for materials needing to be mixed especially intensively

The S 5 EV / EVTM worm pump endless possible uses



Plaster / Fine plaster

Special applications

Exterior plaster

(lime, lime cement and insulating plaster)

Interior plaster (lime plaster)











- Fire protection mortar
- Self-levelling compound
- Masonry, adhesive and refurbishing mortar
- Sealing slurry
- Injection and filling mortar
- Glass-fibre-reinforced concrete
- Rough finish plaster and adhesive bridges (by installing corresponding screw conveyor parts)

The modular system of the S 5 is based on a worm pump with a powerful 5.5 kW drive. The basic version is particularly suitable for users who pump and spray pumpable wet mortars with grain sizes of up to 6 mm.

It provides the basis for the extended S 5 EVTM version with pan mixer. The advantage: You can also retrofit the pan mixer on the S 5 EV. The pan mixer enables you to mix high-quality materials in both cases.

Your authorized Putzmeister dealer will gladly advise you on technical details and application questions.



Central control cabinet is also a power distributor for attached devices such as a pan mixer or compressors



Safety grill with integrated safety switch and wide opening angle provides full access for maintenance and cleaning



The pan mixer is easy to retrofit and ensures maximum mixing quality.

Technical data	S 5 EV	S 5 EVTM
Pan mixer	_	80
Hopper volume	100	100
Pump	Worm pump 2L6	Worm pump 2L6
Delivery rate (theor.)*	7–40 l/min	7–40 l/min
Delivery pressure	25 bar	25 bar
Delivery range**	60 m horizontal, 40 m vertical	60 m horizontal, 40 m vertical
Engine	5.5 kW, 400 V / 50 Hz	5.5 kW, 400 V / 50 Hz
Mixer drive	-	2.2 kW
Weight	190 kg	400 kg
Length × width × height	$2,290\times680\times650~\text{mm}$	$2,505 \times 680 \times 1,150 \text{ mm}$
Filling height	650 mm	1,150 mm
Maximum particle size	6 mm	6 mm
Pressure connection	M 50	M 50
Special feature	Basic version	with pan mixer

Equipment	S 5 EV	S 5 EVTM
Adapter V 50-M35		
Cleaning tool		
Grease cartidge		
Instruction manual and spare parts list		
Seal ring with mortar coupling		
Standard colour paintwork		
Standard tool		
Cable remote control 20 m with emergency switch		
Pneumatic remote control		
Vibrating screen		_
Timing relay for mixer	-	
Water metering	-	

- * The delivery rate depends on the pump model, and can vary in accordance with the pump used.
- ** The data is based on experience and depends on the materials used.

☐ Option ■ Standard

Putzmeister Mörtelmaschinen GmbH

 $\label{eq:max-eyth-Straße} \begin{tabular}{ll} Max-Eyth-Straße 10 \cdot 72631 Aichtal / Germany \\ P.O.Box 2152 \cdot 72629 Aichtal / Germany \\ Tel. +49 7127 599-0 \cdot Fax +49 7127 599-743 \\ mm@putzmeister.com \cdot www.pmmortar.de \\ \end{tabular}$

